



Recommended Installation Height  
From Floor to Top of Hand Dryer = 950mm  
From Floor to Bottom of Hand Dryer = 300mm  
Complies with Disabled Persons Requirements

Electrical Installation Options  
Simple electrical connection by plug and lead as supplied, or can be direct wired by electrician.

## BUSINESS JET DRYER JDBUSI-X [X = S (Silver), W (White)]

### TECHNICAL SPECIFICATIONS

#### Electrical

Input voltage: 230-240V AC, Single Phase 50Hz  
Rated Power: 850W, 5 Amp  
Motor Type: Brushless  
Energy Consumption per use: 0.0035kWh  
Standby Power: 1 W

#### Construction

Polycarbonate – ABS Casing  
Colour Finishes: Silver, White  
Water Protection: IPX1

#### Filtration

Anti-bacterial/Carbon Filter

#### Operation

Infra Red Touch Free Operation  
Hand Drying Time: Approx. 10 - 15 Seconds  
Airflow: 350+ kph  
Operating Noise: Approx. 70 dba  
Water Holding Tank: 500ml

#### Weight

Unit Weight: 11kg  
Packaged Weight: 13kg

#### Warranty

3 year Parts, 1 Year Labour (Limited to 350,000 Uses)

#### Product Certification

Approved to IEC/EN60335-1 and IEC/EN60335-2-23  
Compliant to EMC directive according to EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3 (CTICK N27284)